



THIS IS TO CERTIFY THAT

Sanitary Solutions Group, LLC
1231 Bluff Road, Columbia, SC 29223

is hereby authorized to continue to apply the
3-A Symbol to the models of equipment, conforming to 3-A Sanitary Standards for:

Number 63-04
63-04 (Sanitary Fittings)

set forth below

CIP Models: Fitting models listed below in 304 / 304L / 316 / 316L SS:

Weld Conc Reducer SS31W7 - 3/4"x1/2"-12"x10";
Weld Ecc Reducer SS32W7 - 3/4"x1/2"-12"x10";
Weld U Tee -TA2UBMMM - 1"x0.5"-4"x3";
Weld cross SS9WWWW7 - 0.5"-12";
Weld Tee Long SS7W7 0.5"-12";
Weld Tee Short SS7WW7 - 0.5"-12";
Weld Tee Instr SS7MPS - 0.5"-12";
Weld 45 degree Short SS2WK7 - 0.5"-12";
Weld 45 degree Elbow Long SS2KS7 - 0.5"-12";
Weld 90 degree Elbow Short SS2WCL7 - 0.5"-12";
Weld 90 degree Elbow Long SS2S7 - 0.5"-12";
Weld 90 degree Elbow Long SST2S - 0.5"-4",
Weld Tee Reducing SS7RWWW7 - 0.5"-12";
Clamp Tee SS7MP - 0.5"-12";
Clamp 90° Elbow SS2CMP - 0.5"-12";
Clamp 45° Elbow SS2KMP - 0.5"-12";
Clamped Cross SS9MP - 0.5"-12";
Clamp Concentric Reducer SS31-14MP - 3/4"x1/2"-12"*10";
Clamp Eccentric Reducer SS32-14MP - 3/4"x1/2"-12"*10";
Clamp 180 Degree Elbow SS2WUMP - 0.5"-6";
Weld 180 Degree Elbow SS2WUL7 - 0.5"-6";
Clamp Reducing Tee Short SS7RMP - 3/4"x1/2"-6"x4";
Clamp Vertical Y Tee SS28YMP - 0.5"-8";
Weld Vertical Y Tee SS28Y7 - 0.5"-8";
Clamp Parallel Y Tee SS28LMP - 0.5"-8";
Weld Parallel Y Tee SS28L7 - 0.5"-8";
Clamp & Weld 90DEG ELBOW SS2CM - 0.5"-8";
Clamp & Weld 45DEG ELBOW SS2KM - 0.5"-6";
Clamp End Cap SS16AMP - 0.5"-12";
Bevel End Cap SS16A - 1"-4";

I-Line Female End Cap, SS16AI-15I - 1"-8";
I-Line Male End Cap, SS16AI-14I - 1"-8";
Q-Line Male End Cap, SS16AQ-14Q - 1"-4";
Q-line Female End Cap, SS16W - 0.5"-12";
Clamp Sched 5 End Cap, SS16AMV - 1"-10";

Ferrules:

SS14WMP - 0.5"-12";
SSL14AM7 - 0.5"-12";
SS14MPHT - 0.5"-6";
SS14MPW - 1"-8";
SS14WLMP - 0.5"-12";
SS14WLI - 1"-4";
SS14WI - 1"-4";
SS15WLI - 1"-4";
SS15WI - 1"-4";
SS19MPX - 1"-6";
SS31WMP - 2"x1"-4"x3";
SS14WHQ - 1"-4";
SS14WMV - 1"-8";
SS14WMX - 1"-8";
SS14AJP - 1"-4";
SS15TRFJP - 1"-4";
SS15AJP - 1"-4";
SS16AJP - 1"-4";
SS14AM7V - 1"-6";
SS14AM7X - 1"-4";
SS19MPZ - 0.5"-6";
SS14PRFJP - 1"-4";
SS14WLQ - 1"-4";
SS14WQ - 1"-4";
SS14WIV - 1"-6";
SS15WIV - 1"-6"
SST14AM7 - 1/2" - 6"

Flange Adapters: SS38SL - 1"-8"; SS38W - 1"-8"; SS51-14MP - 1"-6"

COP Models:

Fittings models listed below in 304 / 304L / 316 / 316L SS:

Bevel Seat: SS14TRF - 1"-4"; SS15TRF - 1"-4"; SS14A - 1"-4"; SS15A - 1"-4"

VALID THROUGH: **December 31, 2026**

Meri Beth Wujcik
Executive Director, 3-A sanitary Standards, Inc.

The issuance of this authorization for the use of the 3-A Symbol is based upon the voluntary certification, by the applicant for it, that the equipment listed above complies fully with the 3-A Sanitary Standard(s) designated. Legal responsibility for compliance is solely that of the holder of this Certificate of Authorization, and 3-A Sanitary Standards, Inc. does not warrant that the holder of an authorization at all times complies with the provisions of the said 3-A Sanitary Standards. This in no way affects the responsibility of 3-A Sanitary Standards, Inc. to take appropriate action in such cases in which evidence of nonconformance has been established.

NEXT TPV INSPECTION/REPORT DUE: November 2026